

FAT SHARK

Attitude V5

MODEL FSV1049

USER MANUAL



Revision D 05/11/2019

For more product information, please visit:

www.fatshark.com

All Rights Reserved

Contents

Attitude V5.....	1
MODEL FSV1049.....	1
USER MANUAL.....	1
.....	1
Revision D 05/11/2019.....	1
For more product information, please visit: www.fatshark.com.....	1
All Rights Reserved.....	1
Introduction.....	3
Product Compatibility.....	3
Product Contents.....	3
Carry Case.....	3
.....	3
Attitude Version 5 Headset.....	3
.....	3
18650 Headset Battery Case	
.....	3
.....	3
True Diversity OLED Receiver already installed in the headset	
.....	4
.....	4
Circularly Polarized antenna	
.....	4
.....	4
Patch Antenna	4
.....	4
Controls Diagram.....	4
Controls.....	5
DVR Operation.....	5
AV Cable Pinout.....	6
External video recording.....	6
5.8GHz Diversity OLED Receiver	6
18650 Headset Battery Pack	7
Specifications.....	7
Operational Advice.....	8
Technical Support.....	9
Trouble Shooting.....	9
Warranty.....	10
Introduction.....	3
Product Compatibility.....	3

Product Contents.....	3
Controls Diagram.....	4
Controls.....	5
DVR Operation.....	5
AV Cable Pinout.....	6
External video recording.....	6
5.8GHz Diversity OLED Receiver	6
18650 Headset Battery Pack	7
Specifications.....	7
Operational Advice.....	8
Technical Support.....	9
Trouble Shooting.....	9
Warranty.....	10

Introduction

Congratulations on purchasing the Fat Shark Attitude Version 5 modular OLED FPV goggles with integrated DVR for analog recording. To ensure your continued enjoyment, please take the time to read through this operating manual thoroughly before using.

Product Compatibility

The Attitude has been designed to adhere to established video standards and is compatible with any product also adhering to accepted video standards. Due to the high number of different manufacturers and variation in quality, it's impossible for us to have tested with every product combination and some troubleshooting may be required if mix/matching components. The Attitude Version 5 has been thoroughly tested with both the included receivers and with ImmersionRC products.

IMPORTANT PRODUCT WARNING!

Do not leave the headset exposed to direct sunlight. Sunlight will magnify through the optics and can burn holes in the OLED color filter. This will then appear as white open areas. This will not be covered by warranty. Keep goggles in their protective case when not in use.

Product Contents

Carry Case



**Attitude Version 5 Headset
w/ Face Plate**



18650 Headset Battery Case



**True Diversity OLED
Receiver already
installed in the
headset**



Circularly Polarized antenna



Patch Antenna



Controls Diagram

Controls

Brightness/contrast control: Pressing left/right increases/decreases display contrast. Pressing forward/back increases/decreases display brightness.

RX power switch: The receiver module power is controlled by this switch. Turn off RX module to avoid video conflict with video source via the AV cable.

Channel select: Rocking the channel select switch forward and back will cause the channel to incrementally increase/decrease. Audio beep sounds on channel change. A long beep sounds on channel top and bottom limits. See OLED section for more details.

Low battery warning: Audio warning if input voltage drops below 6.8V

Volume control: There is no volume control - volume level is set at high. Please use with adjustable earphone accessory for volume control

DVR Operation

1. SD card **MUST** be formatted before use to ensure stable recording.
2. DVR is for analog recording only, no HD recording.
3. Do not place alternative files that you want to keep into the DVR. The DVR may not recognize the file space and write over your files. Use dedicated SD card.

Recording:

After powering goggles, turn on DVR by depressing vertically and holding the DVR control button for 1 full second (**long press**).

RED LED should now show solid.

Ensure SD card is inserted and **short press** to start recording (RED LED will slowly FLASH (~2 times/second). Single beep on record start.

Short press again stops recording (turns to solid RED LED). Double beep on record stop.

Playback

Playing back the recording files must disconnect the external receiver and remove the AV in source (preventing OSD menu conflict)

After turning on DVR and in stop record mode (SOLD RED LED) depress and hold DVR button for 1 second (**long press**) to enter menu.

Menu Navigation

Playback (press right to enter)

Now can see: Preview shot with file number

press **up/down** to change file number

press **right** to play

Up/down controls playback speed/direction

Right press pause/play

Left press, back to main menu

Format (press right to enter)

Execute (press right)

Record (press right)

Now can see:

default (no recording until press the button to start)

auto start (auto start recording when power on)

auto start continuous (auto start recording when power on and overwrite the file if space is full)

press **up/down** to select the recording mode

press **right to enter** to confirm

Pressing **left** from main menu exits menu

AV Cable Pinout

3.5mm AV Connector: Yellow: Video,
White: Audio Left, Red: Audio Right



External video recording

Use the AV cable to insert the AV in/out connector on the right side of goggle, and connect the external video recording device to the other end of AV cable (Please refer to the equipment supplier's instructions for the relevant settings).

5.8GHz Diversity OLED Receiver

The Attitude V5 comes with an internal connection to a second antenna port to enable diversity without needing an external cable. The receiver can scan the surrounding channels with one click, automatically detect it at any time during use, and automatically select the stronger one of the two antennas to receive the display.

If you wish to replace the included receiver,

- You should take out the OLED module door. There is a blue FPC cable in the lower right corner of the module.
- Pull the FPC connector to the right, loosen the blue FPC cable
- Take out the OLED receiver, and insert your new module (Rapid Fire)

Module Specifications:

OLED display: Frequency group, channel, frequency / antenna selection indication / RSSI

Button: Select Frequency group/channel/source mode

Power Supply: 3.3~5 V

Sensitivity: ≤ -90 dB

RF Signal level: -90 dBm~+5 dBm

Video format: NTSC/PAL(Auto select)

Operational [environment](#) : -10~65 °C

Channel table as below:

Code	Name	CH1	CH2	CH3	CH4	CH5	CH6	CH7	CH8
F	Band F	5740	5760	5780	5800	5820	5840	5860	5880
R	RaceBand	5658	5695	5732	5769	5806	5843	5880	5917
A	Band A	5865	5845	5825	5805	5785	5765	5745	5827
E	Band E	5705	5685	5665	5645	5885	5905	5925	5945
L	Band L	5362	5399	5436	5473	5510	5547	5584	5621
AV in	AV in mode	closed	closed	closed	closed	closed	closed	closed	closed

18650 Headset Battery Pack

The Fat Shark headset battery pack with a row of stylish blue LED indicators allows you to visually check its remaining capacity (4 levels) to prevent a sudden power/vision lost. Large capacity pretty much lets you fly all day. It seats securely in the headset strap pocket. The soft silicone battery cable extends out of the top of the pack to avoid contact with head strap. Barrel connector cable features high strand count wire for flexibility and long life. Wire stress is minimized by the additional rubber gasket around the cable exit.



Specifications

Headset Specifications:

Optic Engine:

Field of View (FOV)	30°
Inter-pupillary Distance (IPD)	59 - 69mm (adjustable)
Diopter Lens Slot:	Available (lens purchased separately)
Display	Resolution 640 x 400 OLED
Video formats	NTSC / PAL auto selection

Electrical:

DVR	Analog video recording SD card support to 32GB (AVI file) Support playback recording file Firmware upgrade via SD card Auto save recording file when power off
Wireless Receiver	True Diversity Receivers with OLED display (Auto Scan Channel / Spectrum Analyzer)
Interfaces:	DC Power port AV in/out port Earphone Jack
Color:	Green and Black
Fan Plate:	Face foam and velcro sticker (easy replacement) Anti-fogging mini fan
Accessories	Attitude V5 OLED Headset 5.8GHz Diversity receiver with OLED display 5.8GHz SpiroNET Circular Polarized antenna 5.8GHz FS RHCP patch antenna 18650 Li-ion Battery Case Zipper case for carrying
Mechanical:	
Dimensions	168 x 83 x 71mm
Weight	193g
Package Size	215*136*87mm

Operational Advice

- **For best performance**, select a channel that has the least amount of interference. While the transmitter is turned OFF, turn on the video headset and look at the screen as you check each channel. Clear channels will have a consistent static background. Channels with interference will have horizontal static lines.
- **Always perform a range test before flying**. This includes AV and RC controls. Some RC receivers can be affected by the proximity of other electronic devices particularly the AV TX.
- Try to space out your components as much as possible to avoid interference to your RC control range (keep stuff away from RX)
- Until experienced, practice flying in a familiar area to avoid becoming disorientated.
- Due to antenna characteristics, there is a “null” in line with antenna direction. You may experience excessive video breakup when flying overhead
- 5.8GHz signal strength drops off very fast stay safely within solid AV range.

- **For maximum distance** it is very important that a clear line of sight exists between the transmitter and the video headset. 2 of the worst causes of interference are human bodies and reinforced concrete.
- Place your TX antenna in open area in a vertical orientation
- **Multipathing** (reflections off buildings/ tall objects) causes signal cancellation and result in broken video. Fly in open areas away from buildings or other tall structures (i.e. barns, hills).
- The headset may become warm to touch during use particularly in the top center region. This is normal. If you are unsure, run the headset for 30 minutes before flying to ensure normal operation.
- Even if you don't require any license to operate this device, you are still legally responsible for operating in a responsible manner.

Technical Support

Documentation/ troubleshooting: <http://fatshark.helpscoutdocs.com/>

Support: support@fatshark.com

Note support should be attempted in the following manner. Initial enquiries to Fat Shark support will expect you to have exhausted the online and retailer resources:

- 1) Research Fat Shark helpdocs.
- 2) Contact retailer for support.
- 3) email Fat Shark support.

Trouble Shooting

Observation	Possible Cause/Solution
No image, display is completely dark	- No power supplied. Check power connections.
No image, display is glowing dark grey	- If using wireless module, turn on RX power on bottom of headset. - If using AV in cable, check video source. - Ensure TX is on and camera connections solid
Lots of interference lines (horizontal lines) with 2.4Ghz receiver	- Choose a cleaner channel. - Change to 5.8Ghz AV - Check correct frequency antenna is used
Poor image, dark or not enough contrast	- Adjust display with contrast/brightness button
Lots of interference lines (horizontal lines) when using 5.8Ghz receiver	Check to see if cause is harmonic interference from 2.4Ghz RC controller (turn radio on/off). - Use CH1 on TX/headset (Ch1 not affected by 2.4Ghz) - check correct frequency antenna is used
Head tracker not working (no response or beeping)	- Ensure module pins are aligned correctly into headset socket
Short range	- Ensure correct antenna are installed - Check for other sources of interference - Ensure transmitter has clear LOS to headset. Test in wide open area, away from any obstructions
Short range (con't)	- Ensure that a compatible antenna is installed. 2.4Ghz

	<p>must use a 2.4Ghz antenna and 5.8Ghz must use a 5.8Ghz antenna</p> <ul style="list-style-type: none"> - do not use other manufacture antenna, they may be dual band or may be reverse SMA (no center pin to connect to receiver)
White dots on LCD display	You were careless and left goggles exposed to sun. Sun burnt off LCD color filter.
Lens fogs up	<p>Cooler optical lens are heated by your humid face causing condensation.</p> <ul style="list-style-type: none"> - Power anti-fog mini fan on faceplate from headset battery, each time press the button can run 8-10m.
Head tracker does not work (can enter menu)	<ul style="list-style-type: none"> - Radio doesn't support selective trainer function - Settings incorrect - Trainer switch on RC controller not activated - In Pause mode
Head tracker drifts or has excessive error correction (jumpy)	<ul style="list-style-type: none"> - Operating inside so compass sensor not correct (use outside) - RC radio interfering with compass sensor (keep RC controller antenna away from headset) - Standing near large metal object (such as a car)

Warranty

The system can be exchanged for a new unit within 7 days for any manufacturing defects if returned in new condition. The video headset will be warranted for repair for 2 years if no signs of excessive use. Buyer will be responsible for shipping costs. If beyond the warranty period we will provide repair services.