

5106A

5108A

5107A

5182A

5106

4611

5120A

5180A

5119

5116

7715

7710

7711

7711A

7711G

7811G

7811

7711X

7713X

X-Maxx® (Model 77086-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically

n in bold are optional accessories. Part categories and individual part listings a	re arranged a	alphabetically.
Bearings & Bushings		Differential Components
Ball bearing, black rubber sealed (15x24x5mm) (2)	7781X	Carrier, differential (aluminum) (requires #7783X spider gear shaft)
Ball bearing, black rubber sealed (15x26x5mm) (2)	7781	Carrier, differential/ x-ring gaskets (2)/ ring gear gasket/ 6x10x0.5 TW
Ball bearing, black rubber sealed (17x26x5mm) (2)	5136X	Differential oil kit (1 each: 10K, 30K, 50K weights)
Ball bearing, black rubber sealed (20x27x4mm) (2)	7782	Gear set, differential (output gears (2)/ spider gears (4)/
Ball bearing, blue rubber sealed (15x24x5mm) (2)		16x23.5x.5mm TW (2))
Ball bearings (5x11x4mm) (2)	5041	Grease, premium high performance (20cc)
Ball bearings, black rubber sealed (12x18x4mm) (2)	7780	Housing, differential (front/rear)
Ball bearings, black rubber sealed (6x13x5mm) (2)	5040	Oil, differential (20M wt) (standard)
Ball bearings, blue rubber sealed (10x15x4mm) (2)	7790	Pinion gear, differential, 11-tooth (front) (heavy duty) (use with #7792
Ball bearings, blue rubber sealed (5x11x4mm) (2)	7791	35-tooth differential ring gear) Pinion gear, differential, 11-tooth (rear) (heavy duty) (use with #7792
Body & Accessories	1191	35-tooth differential ring gear)
Body mounts, front & rear/3x15mm BCS (1)/ 3x12mm shoulder screw	7792	Ring gear, differential, 35-tooth (heavy duty) (use with #7790, #7791
(2)/ 3x10mm flat-head machine screw (6)/ 3x15mm flat-head machine		11-tooth differential pinion gears)
screw (2)	7783	Spider gear shaft (2)/ spacers (4)/ 16x23.5x.5mm TW (2)
Body reinforcement set (fits #7711 body)	7783X	Spider gear shaft (2)/ spacers (4)/16x23.5x.5 stainless washer (2) (for
Body support, rear/ 3x15mm CS (2) / 3x15mm flat-head machine (2)		#7781X aluminum differential carrier)
(fits X-Maxx®)		Driveline Components
Body, X-Maxx® (clear, trimmed, requires painting)/ window	7752	
masks/ decal sheet	7794	Cush drive key/ nin/ elastomer damper
Body, X-Maxx®, blue (painted, decals applied) (assembled with front & rear body mounts, rear body support, and tailgate protector)	7794 7754X	Cush drive key/ pin/ elastomer damper Drive cup (1)/ 3x8mm CS (use only with #7750X driveshaft)
Body, X-Maxx®, green (painted, decals applied) (assembled with	7755	Driveshaft assembly, center, aluminum
front & rear body mounts, rear body support, and tailgate protector)	7750X	Driveshaft, steel constant-velocity (heavy duty, shaft only, 160mm) (1)
Body, X-Maxx®, green (painted, decals applied) (assembled with	11000	(replacing #7750 also requires #7751X, #7754X and #7768, #7768R,
front & rear body mounts, rear body support, and tailgate protector)		or #7768G)
Body, X-Maxx®, orange (painted, decals applied) (assembled with	5040	Oil, differential (20M wt) (standard)
front & rear body mounts, rear body support, and tailgate protector)	7751X	Rebuild kit, steel constant-velocity driveshaft (includes pins for 2
Body, X-Maxx®, ProGraphix® (graphics are printed, requires		driveshaft assemblies (use only with #7750X driveshaft)
paint & final color application)/ decal sheet	7768A	Stub axle, aluminum (black-anodized) (1) (use only with #7750X
Body, X-Maxx®, red (painted, decals applied) (assembled with front &		driveshaft)
rear body mounts, rear body support, and tailgate protector)	7768	Stub axle, aluminum (blue-anodized) (1) (use only with #7750X
Body, X-Maxx®, red (painted, decals applied) (assembled with front &		driveshaft)
rear body mounts, rear body support, and tailgate protector)	7768G	Stub axle, aluminum (green-anodized) (1) (use only with #7750X
Body, X-Maxx®, Rock n' Roll (painted, decals applied) (assembled with tailgate protector)	7768R	driveshaft) Stub axle, aluminum (red-anodized) (1) (use only with #7750X
Tailgate protector/ 3x8mm flat-head screw (4)	11001	driveshaft)
	7758A	Wheel nuts, splined, 17mm, serrated (black-anodized) (4)
Bumpers & Skidplates	7758	Wheel nuts, splined, 17mm, serrated (blue-anodized) (4)
Bumper mount, front/ bumper support	7758G	Wheel nuts, splined, 17mm, serrated (green-anodized) (4)
Bumper mount, rear/ bumper support	7758T	Wheel nuts, splined, 17mm, serrated (orange-anodized) (4)
Bumper, front	7758R	Wheel nuts, splined, 17mm, serrated (red-anodized) (4)
Bumper, rear		Front Suspension & Steering
Skidplate, center	7700	
Skidplate, front (1), rear (1)/ rubber impact cushion (2)	7726 7721	Bulkhead tie bar, upper (1)/ lower (2) (steel)
Chassis & Attachments	7720	Bulkhead, front (lower) Bulkhead, front (upper)
Battery hold-down (2)/ foam pad (2)	7752	Carriers, stub axle (left & right)
Battery hold-down mounts, left (2)/ right (2)/ 3x18mm CS (4)	7732	Caster blocks (c-hubs), left & right
Body mounts, front & rear/3x15mm BCS (1)/ 3x12mm shoulder screw	7716	Mount, tie bar, front (1)/ rear (1)
(2)/ 3x10mm flat-head machine screw (6)/ 3x15mm flat-head machine	7747	Servo horn, steering/ linkage, steering (46mm, assembled with pivot
screw (2)		balls)
Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15	7739	Shock tower, front (left & right halves)
CS (4) Rumper mount_front/ humper support	7746	Steering bellcranks/ bellcrank support/servo saver/ servo saver
Bumper mount, front/ bumper support	-	spring/ draglink/ 3x20mm shoulder screws (2)
Bumper mount, rear/ bumper support	7737	Steering blocks, left & right
Bumper, front	7746X	Steering link, steel/ servo saver spring, heavy duty (use with
Bumper, rear Chassis		#2085X metal gear servo)
Chassis Chassis top brace	7831	Suspension arm, black, lower (left, front or rear), heavy duty (1)
Nerf bars, chassis (2)	7830	Suspension arm, black, lower (right, front or rear), heavy duty (1)
Seal kit, receiver box (includes o-ring, seals, and silicone grease)	7829	Suspension arm, black, upper (left or right, front or rear), heavy
Skidplate, center	70041	duty (2) Supremains any blue lower (left front or rear) becauduty (4)
Skidplate, front (1), rear (1)/ rubber impact cushion (2)	7831X	Suspension arm, blue, lower (left, front or rear), heavy duty (1)
Spacer, battery compartment (2)/ foam blocks (4)/ foam pad (2)	7830X	Suspension arm, blue, lower (right, front or rear), heavy duty (1)
Wheelie bar, black (assembled)	7831G 7830G	Suspension arm, green, lower (left, front or rear), heavy duty (1)
Wheels (2) (for #7776 wheelie bar)	10300	Suspension arm, green, lower (right, front or rear), heavy duty (1)
Cush Drive Components	7831T	Suspension arm, orange, lower (left, front or rear), heavy duty (1)
	7830T	Suspension arm, orange, lower (right, front or rear), heavy duty (r)
Cush drive key/ pin/ elastomer damper		(1)
Housing, cush drive (front & rear halves)	7831R	Suspension arm, red, lower (left, front or rear), heavy duty (1)
Spur gear, 46-tooth, steel (wide-face, 1.0 metric pitch)	7830R	Suspension arm, red, lower (right, front or rear), heavy duty (1)

7830R

Suspension arm, red, lower (right, front or rear), heavy duty (1) 7831A

Suspension arm, white, lower (left, front or rear), heavy duty (1) Suspension arm, white, lower (right, front or rear), heavy duty (1)

	paint & final color application)/ decal sheet
7711R	Body, X-Maxx®, red (painted, decals applied) (assembled with front a
// I IK	rear body mounts, rear body support, and tailgate protector)
7811R	Body, X-Maxx®, red (painted, decals applied) (assembled with front a
70111	rear body mounts, rear body support, and tailgate protector)
7711T	Body, X-Maxx®, Rock n' Roll (painted, decals applied)
	(assembled with tailgate protector)
7712	Tailgate protector/ 3x8mm flat-head screw (4)
	Bumpers & Skidplates
7733	Bumper mount, front/ bumper support
7734	Bumper mount, rear/ bumper support
7735	Bumper, front
7736	Bumper, rear
7745	Skidplate, center
7744	Skidplate, front (1), rear (1)/ rubber impact cushion (2)
//44	
	Chassis & Attachments
7719	Battery hold-down (2)/ foam pad (2)
7718	Battery hold-down mounts, left (2)/ right (2)/ 3x18mm CS (4)
7715	Body mounts, front & rear/3x15mm BCS (1)/ 3x12mm shoulder screw
	(2)/ 3x10mm flat-head machine screw (6)/ 3x15mm flat-head machin
	screw (2)
7724	Box, receiver (sealed)/ wire cover/ foam pads/ silicone grease/ 3x15 CS (4)
7733	Bumper mount, front/ bumper support
7734	Bumper mount, rear/ bumper support
7735	Bumper, front
7736	Bumper, rear
7722	Chassis
7714X	Chassis top brace
7723	Nerf bars, chassis (2)
7725	Seal kit, receiver box (includes o-ring, seals, and silicone grease)
7745	Skidplate, center
7744	Skidplate, front (1), rear (1)/ rubber impact cushion (2)
7717X	Spacer, battery compartment (2)/ foam blocks (4)/ foam pad (2)
7776	Wheelie bar, black (assembled)
7775	Wheels (2) (for #7776 wheelie bar)
	Cush Drive Components
7794	Cush drive key/ pin/ elastomer damper
7793X	Housing, cush drive (front & rear halves)
6447R	Spur gear, 46-tooth, steel (wide-face, 1.0 metric pitch)
6448R	Spur gear, 50-tooth, steel (wide-face, 1.0 metric pitch)
6449X	Spur gear, 54-tooth, steel (1.0 metric pitch)
	Spur gear, 54-tooth, steel (wide-face, 1.0 metric pitch)

7830A

Page 2 X-Maxx®: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 77086-4) Parts List

	X-Maxx®: TQi Traxxas Link Enabled 2.4GHz Radio	
7829X	Suspension arms, blue, upper (left or right, front or rear), heavy	7
7829G	duty (2) Suspension arms, green, upper (left or right, front or rear), heavy	7
7731	duty (2) Suspension arms, lower (left, front or rear) (1)	
7730	Suspension arms, lower (right, front or rear) (1)	
7829T	Suspension arms, orange, upper (left or right, front or rear),	2
7829R	heavy duty (2) Suspension arms, red, upper (left or right, front or rear), heavy	2 2
	duty (2)	2
7729	Suspension arms, upper (left or right, front or rear) (2)	2
7829A	Suspension arms, white, upper (left or right, front or rear), heavy duty (2)	2
7743	Suspension pin retainer (4)	
7740	Suspension pin set, front or rear corner (hardened steel), 4x85mm	29
	(1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set)	6
7742	Suspension pin set, shock mount (front or rear, hardened steel),	2
7741	4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2)	2
	Hardware	
2585	Cylinder head bolts, marine 3x20mm CS (6) (TRX 2.5)	2
2585	Head screws, 3x12mm cap-head machine (hex drive) (6) (TRX 2.5,	2
2001	2.5R, 3.3)	-
2586	Head screws, 3x15mm cap-head machine (hex drive) (6) (TRX 2.5)	2
4955	Pins, axle (2.5x12mm) (4)	_
3234 2577	Screws, 2.5x14mm cap-head machine (hex drive) (6) Screws, 3x10mm button-head machine (hex drive) (6)	2
2577 2587	Screws, 3x10mm button-nead machine (nex drive) (6) Screws, 3x10mm cap-head machine (6) (no washer)	2
4859	Screws, 3x10mm flat-head machine (b) (no washer)	_
2593	Screws, 3x14mm button-head machine (hex drive) (6)	2
2579	Screws, 3x15mm button-head machine (hex drive) (6)	~
3646	Screws, 3x15mm flat-head machine (hex drive) (6)	6 2
4857 2581	Screws, 3x20mm countersunk machine (hex drive) (6) Screws, 3x25mm button-head machine (hex drive) (6)	2
2575	Screws, 3x6mm button-head machine (hex drive) (6)	2
2576	Screws, 3x8mm button-head machine (hex drive) (6)	
2535	Screws, 4x10mm countersunk machine (hex drive) (6)	2
3937	Screws, 4x12mm button-head machine (hex drive) (6)	6
3938	Screws, 4x14mm button-head machine (hex drive) (6)	6
2594 2546	Screws, 4x15mm button-head machine (hex drive) (6) Screws, 4x15mm countersunk machine (hex drive) (6)	
3933	Screws, 4x16mm button-head machine (hex drive) (6)	6
2597	Screws, 4x22mm button-head machine (hex drive) (6)	6
2596	Screws, 4x25mm button-head machine (hex drive) (6)	6 6
2598X	Screws, 4x30mm button-head machine (hex drive) (6)	2
2595 2743	Screws, 4x35mm button-head machine (hex drive) (6) Set (grub) screws, 3mm hardened (12)	2
3642X	Shoulder screws, Ultra Shocks (3x12 hex drive) (6)	
5480X	Wheel wrench, splined, 17mm	2
	LED Lights	6
7882	Extension harness, LED lights (high-voltage)	6
6590	High-Voltage Power Amplifier	~
7884	LED light bar, front (high-voltage) (40 white LEDs (double row),	6 6
7883	82mm wide) (fits X-Maxx® or Maxx®) LED light bar, rear, red (with white reverse light) (high-voltage)	0
,	(24 red LEDs, 24 white LEDs, 100mm wide)/ light bar mount (fits	6
	X-Maxx® or Maxx®)	~
7885	LED light kit, complete (includes #6590 high-voltage power amplifier)	6
	Motors & Electronics	6
7749	Adapter, standard servo (adapts standard servo to fit in X-Maxx®	0
	or Maxx®)	6
3475	Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s)	
7787 3474	Covers, gear (3) Dual cooling fan kit (with shroud), Velineon® 1200XL motor	6
2087	Gear set (for 2085 servo)	6
2001	Gear set, metal (for 2085 & 2085X servos)	
2087X		7
2087X 3362	Heat sink, Velineon® 1600XL	
2087X 3362 7760	Motor mounts (front and rear)/ pins (2)	'
2087X 3362 7760 3491	Motor mounts (front and rear)/ pins (2) Motor, Velineon® 1200XL, brushless	/
2087X 3362 7760 3491 2086	Motor mounts (front and rear)/ pins (2) Motor, Velineon® 1200XL, brushless Servo case/gaskets (for 2085 & 2085X servos)	1
2087X 3362 7760 3491	Motor mounts (front and rear)/ pins (2) Motor, Velineon® 1200XL, brushless Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx®	
2087X 3362 7760 3491 2086	Motor mounts (front and rear)/ pins (2) Motor, Velineon® 1200XL, brushless Servo case/gaskets (for 2085 & 2085X servos)	7
2087X 3362 7760 3491 2086 2085 2085X	Motor mounts (front and rear)/ pins (2) Motor, Velineon® 1200XL, brushless Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link	7 7
2087X 3362 7760 3491 2086 2085	Motor mounts (front and rear)/ pins (2) Motor, Velineon® 1200XL, brushless Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Velineon® VXL-8s Electronic Speed Control, waterproof (brushless)	7 7 7
2087X 3362 7760 3491 2086 2085 2085X	Motor mounts (front and rear)/ pins (2) Motor, Velineon® 1200XL, brushless Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Velineon® VXL-8s Electronic Speed Control, waterproof (brushless) (fwd/rev/brake)	7 7 7 7 7
2087X 3362 7760 3491 2086 2085 2085X 3496	Motor mounts (front and rear)/ pins (2) Motor, Velineon® 1200XL, brushless Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Velineon® VXL-8s Electronic Speed Control, waterproof (brushless)	7" 7" 7

7759G	Washers, motor mount, aluminum (green-anodized) (4)/ 4x18mm
	BCS (4)
7759R	Washers, motor mount, aluminum (red-anodized) (4)/ 4x18mm BCS (4)
	Radio System, Batteries & Chargers
2854X	10000mAh 7.4v 2-Cell 25C LiPo Battery
2872X	5000mAh 11.1v 3-Cell 25C LiPo Battery
2889X	5000mAh 14.8v 4-Cell 25C LiPo Battery
2857X	6400mAh 11.1v 3-Cell 25C LiPo Battery
2890X 2878X	6700mAh 14.8v 4-Cell 25C LiPo Battery 8400mAh 11.1v 3-Cell 25C LiPo Battery
2070A 2938X	Adapter, Traxxas® iD® LiPo battery (adapts Traxxas iD batteries
23307	to separate balance ports)
2943	Battery charge indicators (green (4), blue (4), grey (4))
6548	Battery door, transmitter (replacement for #6516, 6517, 6528, 6529,
	6530 transmitters)
2914	Battery, Power Cell AA Alkaline (4)
2993	Battery/charger completer pack (includes #2971 iD® charger (1),
	#2890X 6700mAh 14.8V 4-cell 25C LiPo battery (2))
2990	Battery/charger completer pack (includes #2972 Dual iD®
	charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo battery (2))
2997	Battery/charger completer pack (includes #2973 Dual iD charger (1), #2890X 6700mAh 14.8V 4-cell 25C LiPo battery (2))
2072	
2972	Charger, EZ-Peak® Dual, 100W, NiMH/LiPo with iD® Auto Battery Identification
2973	Charger, EZ-Peak® Live Dual, 200W, NiMH/LiPo with iD® Auto
	Battery Identification
2971	Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery
	Identification
2970	Charger, EZ-Peak® Plus, 4 amp, NiMH/LiPo with iD® Auto
	Battery Identification
6525	Communication link, telemetry expander
2087	Gear set (for 2085 servo)
2087X 2968X	Gear set, metal (for 2085 & 2085X servos)
29007	LiPo cell voltage checker/balancer (includes #2938X adapter for Traxxas® iD® batteries)
2968	LiPo cell voltage checker/balancer (requires #2938X adapter for
2000	Traxxas® iD® batteries)
6533	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel)
6552	Seal kit, expander box (includes o-ring, seals, and silicone
	grease)
6526	Sensor, auto-detectable, temperature
6527	Sensor, auto-detectable, voltage
6531	
0001	Sensor, temperature & voltage (fits X-Maxx®)
6521	Sensor, temperature & voltage (fits X-Maxx®) Sensor, temperature and voltage (long)
6521	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx®
6521 2086 2085	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount)
6521 2086	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/
6521 2086 2085 2085X	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link
6521 2086 2085 2085X 6553X	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system
6521 2086 2085 2085X	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with
6521 2086 2085 2085X 6553X 6550X	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module)
6521 2086 2085 2085X 6553X 6550X	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system
6521 2086 2085 2085X 6553X 6550X	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module)
6521 2086 2085 2085X 6553X 6550X	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system Telemetry GPS module 2.0, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™
6521 2086 2085 2085X 6553X 6550X 6550 6551X 6550R	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver)
6521 2086 2085 2085X 6553X 6550X 6550 6551X	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system Telemetry expander, TQi radio system Telemetry GPS module 2.0, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas
6521 2086 2085 2085X 6553X 6550X 6550 6551X 6550R	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro
6521 2086 2085 2085X 6553X 6550X 6550 6551X 6509R 6507R	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver)
6521 2086 2085 2085X 6553X 6550X 6550 6551X 6550R	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2-
6521 2086 2085 2085X 6553X 6550X 6550 6551X 6509R 6509R 6507R	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system Telemetry GPS module 2.0, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only)
6521 2086 2085 2085X 6553X 6550X 6550 6551X 6509R 6507R	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-
6521 2086 2085 2085X 6553X 6550X 6550 6551X 6509R 6509R 6507R	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system Telemetry GPS module 2.0, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only)
6521 2086 2085 6553X 6550X 6550X 6550R 6551X 6509R 6509R 6528 6528 6529	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system Telemetry expander, TQi radio system Telemetry expander, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only)
6521 2086 2085 6553X 6550X 6550X 6550R 6551X 6509R 6509R 6528 6528 6529	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4-
6521 2086 2085 6553X 6550X 6551X 6550R 6509R 6507R 6528 6529 6530	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry gender, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only) Traxxas Link™ Wireless Module
6521 2085 2085 6553X 6550 6551X 6509R 6509R 6507R 6528 6528 6529 6530 6511	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only) Traxxas Link™ Wireless Module
6521 2085 2085 6553X 6550X 6551X 6550R 6509R 6507R 6528 6529 6530	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander .TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only) Traxxas Link™ Wireless Module <u>Reatly-To-Race Motle</u> X-Maxx®: Brushless Electric Monster Truck with TQi Traxxas Link™
6521 2086 2085 6553X 6550X 6550 6551X 6509R 6509R 6528 6528 6529 6530 6511	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only) Traxxas Link™ Wireless Module
6521 2086 2085 6553X 6550X 6550 6551X 6509R 6509R 6528 6528 6529 6530 6511	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3- channel (transmitter only) Traxas Link™ Wireless Module <u>Cently-To-Race Motle</u> X-Maxx®: Brushless Electric Monster Truck with TQi Traxxas Link™ Enabled 2.4GHz Radio System & Traxxas Stability Management (TSM)®
6521 2086 2085 2085X 6550X 6550X 6551X 6509R 6507R 6528 6529 6530 6511 77086-4	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander .TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only) Traxxas Link™ Wireless Module Leatly-Do-Race Motle X-Maxx®: Brushless Electric Monster Truck with TQi Traxxas Link™ Enabled 2.4GHz Radio System & Traxxas Stability Management (TSM)®
6521 2086 2085 2085X 6550X 6550X 6550R 6550R 6507R 6528 6529 6530 6511 77086-4	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3- channel (transmitter only) Traxas Link™ Wireless Module Rechtyero. X-Maxx®: Brushless Electric Monster Truck with TQi Traxxas Link™ Enabled 2.4GHz Radio System & Traxxas Stability Management (TSM)® Bulkhead tie bar, upper (1)/ lower (2) (steel)
6521 2086 2085 2085X 6550X 6550X 6551X 6509R 6507R 6528 6529 6530 6511 77086-4	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3- channel (transmitter only) Traxxas Link™ Wireless Module ECELUY-TO-RECE MOILE X-Maxx®: Brushless Electric Monster Truck with TQi Traxxas Link™ Enabled 2.4GHz Radio System & Traxxas Stability Management (TSM)® Bulkhead tie bar, upper (1)/ lower (2) (steel) Bulkhead tie bar, upper (1)/ lower (2) (steel) Bulkhead, rear (upper & lower), center differential (replacing #7727 &
6521 2086 2085 2085X 6553X 6550X 6550 6551X 6509R 6507R 6528 6529 6530 6511 77086-4	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/ servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only) Traxsas Link™ Wireless Module Belike 2.4GHz Radio System & Traxxas Stability Management (TSM)® Bulkhead tie bar, upper (1)/ lower (2) (steel) Bulkhead, rear (upper & lower), center differential (replacing #7727 & #7728 requires #5107A ball bearings (2))
6521 2086 2085 2085X 6550X 6550X 6550R 6507R 6528 6529 6530 6511 77086-4	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Tarasmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2-channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4-channel (transmitter only) Trassmitter, TQi Traxas Link™ enabled, 2.4GHz high output, 4-channel (transmitter only) Trassmitter, TQi Traxas Link™ enabled, 2.4GHz high output, 4-channel (transmitter only) Trassmitter, TQi Traxas Link™ enabled, 2.4GHz high output, 4-channel (transmitter only) Trassmit
6521 2086 2085 2085X 6550X 6550X 6550X 6550R 6507R 6528 6529 6530 6511 77086-4	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander 7.0 radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi Taxxas Link™ Wireless Module, Z.4GHz high output, 2-channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-channel (transmitter only) Traxxas Link™ Wireless Module Reatify=Construct Monster Truck with TQi Traxxas Link™ Enabled 2.4GHz Radio System & Traxxas Stability Management (TSM)® Bulkhead tie bar, upper (1)/ lower (2) (steel) </td
6521 2086 2085 2085X 6550X 6550X 6550R 6507R 6507R 6528 6529 6530 6511 77086-4	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) Tqi 1.4 GHz High Output radio system, 4-channel with Traxxas Link™ wireless Module, TSM (4-ch transmitter, 5-ch micro receiver) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4-channel (transmitter only) Traxxas Link™ Wireless Module Reatify Definition Reatify Definition Servere Reatify Definitio
6521 2086 2085X 6553X 6550X 6550R 6550R 6509R 6528 6529 6530 6511 77086-4 7726 77752 7716	Sensor, temperature and voltage (long) Servo case/gaskets (for 2085 & 2085X servos) Servo, digital high-torque (ball bearing), waterproof (X-Maxx®/Maxx® mount) Servo, digital high-torque, metal gear (ball bearing), waterproof/servo saver spring/ steering link Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander 7.0 radio system (compatible only with #6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ enabled, TSM (2-ch transmitter, 5-ch micro receiver) TQi Taxxas Link™ Wireless Module, Z.4GHz high output, 2-channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-channel (transmitter only) Traxxas Link™ Wireless Module AcAtify_Dot_Dot_Rece Motife X-Maxx®: Brushless Electric Monster Truck with TQi Traxxas Link™ Enabled 2.4GHz Radio System & Traxxas Stability Management (TSM)®

Page 3 X-Maxx®: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 77086-4) Parts List

•		
7829	Suspension arm, black, upper (left or right, front or rear), heavy duty (2)	
7831X	Suspension arm, blue, lower (left, front or rear), heavy duty (1)	64
7830X	Suspension arm, blue, lower (right, front or rear), heavy duty (1)	64
7831G	Suspension arm, green, lower (left, front or rear), heavy duty (1)	04
7830G	Suspension arm, green, lower (right, front or rear), heavy duty	-
	(1)	64
7831T		
	Suspension arm, orange, lower (left, front or rear), heavy duty (1)	64
7830T	Suspension arm, orange, lower (right, front or rear), heavy duty	
	(1)	64
7831R	Suspension arm, red, lower (left, front or rear), heavy duty (1)	-0-
7830R	Suspension arm, red, lower (right, front or rear), heavy duty (1)	
7831A	Suspension arm, white, lower (left, front or rear), heavy duty (1)	64
7830A	Suspension arm, white, lower (right, front or rear), heavy duty (1)	
		64
7829X	Suspension arms, blue, upper (left or right, front or rear), heavy	
	duty (2)	64
7829G	Suspension arms, green, upper (left or right, front or rear), heavy	
	duty (2)	64
7731	Suspension arms, lower (left, front or rear) (1)	-0-
7730	Suspension arms, lower (right, front or rear) (1)	
7829T	Suspension arms, orange, upper (left or right, front or rear),	64
10291		
	heavy duty (2)	64
7829R	Suspension arms, red, upper (left or right, front or rear), heavy	
	duty (2)	64
7729	Suspension arms, upper (left or right, front or rear) (2)	64
7829A	Suspension arms, white, upper (left or right, front or rear), heavy	64
	duty (2)	
7743	Suspension pin retainer (4)	64
7740	Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm	
7740		
	(1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set)	51
7742	Suspension pin set, shock mount (front or rear, hardened steel),	51
	4x25mm (2), 4x38mm (2)	77
7741	Suspension pins, 4x85mm (hardened steel) (2)	
	Shocks (GTX)	77
7765A	Body, GTX shock (aluminum, black-anodized) (1)	77
7765	Body, GTX shock (aluminum, blue-anodized) (1)	
7765G	Body, GTX shock (aluminum, green-anodized) (1)	77
7765R	Body, GTX shock (aluminum, red-anodized) (1)	
7765X	Body, GTX shock (hard-anodized, PTFE-coated aluminum) (1)	77
7762	Rebuild kit, GTX shocks (lower cartridge, assembled, pistons, piston	•••
	nuts, bladders) (renews 2 shocks)	
7763	Shaft, GTX shock, 110mm (assembled with rod ends & hollow balls)	77
1100	(steel, chrome finish) (2)	
7763T	Shaft, GTX shock, TiN-coated (2) (assembled with rod ends and	
11001	steel hollow balls)	77
7764A	Shock caps, aluminum (blue-anodized), GTX shocks (4)/ spacers	
11044	(8)	
7764G	Shock caps, aluminum (green-anodized), GTX shocks (4)/	
11040	spacers (8)	
		77
7764X	Shock caps, aluminum (hard-anodized, PTFE-coated), GTX	
	shocks (4)/ spacers (8)	
7764R	Shock caps, aluminum (red-anodized), GTX shocks (4)/ spacers	
	(8)	77
7764	Shock caps, GTX shocks/ spring perch/ adjusters/ 2.5x14mm CS (2)	_
	(for 2 shocks)	77
7761A	Shocks, GTX, aluminum (black-anodized) (fully assembled w/o	77
	springs) (2)	
7761	Shocks, GTX, aluminum (blue-anodized) (fully assembled w/o	77
1101	springs) (2)	
77640		77
7761G	Shocks, GTX, aluminum (green-anodized) (fully assembled w/o	77
	springs) (2)	
7761R	Shocks, GTX, aluminum (red-anodized) (fully assembled w/o springs)	
	(2)	77
1667	Silicone shock oil (30 wt), 60cc	
7767	Spring retainer (adjuster), blue-anodized aluminum, GTX shocks	
	(4) (assembled with o-ring)	77
7767G	Spring retainer (adjuster), green-anodized aluminum, GTX	
	shocks (4) (assembled with o-ring)	
7767X	Spring retainer (adjuster), PTFE-coated aluminum, GTX shocks	77
77675	(4) (assembled with o-ring)	
7767R	Spring retainer (adjuster), red-anodized aluminum, GTX shocks	
	(4) (assembled with o-ring)	
7853	Springs, shock (natural finish) (GTX) (0.824 rate) (2)	25
7854	Springs, shock (natural finish) (GTX) (0.929 rate) (2)	99
7766	Springs, shock (natural finish) (GTX) (1.055 rate) (2)	99
7855	Springs, shock (natural finish) (GTX) (1.199 rate) (2)	95
7856	Springs, shock (natural finish) (GTX) (1.346 rate) (2)	
7857	Springs, shock (natural finish) (GTX) (1.546 rate) (2)	77
7858	Springs, shock (natural finish) (GTX) (1.538 rate) (2)	
		77

	Spur Gears & Pinion Gears
6484X	Gear, 11-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
	(compatible with steel spur gears)
6485X	Gear, 12-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
	(compatible with steel spur gears)
6486X	Gear, 13-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
	(compatible with steel spur gears)
6488X	Gear, 14-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
	(compatible with steel spur gears)
6487X	Gear, 15-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
	(compatible with steel spur gears)
6489X	Gear, 16-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
	(compatible with steel spur gears)
6490X	Gear, 17-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
C404V	(compatible with steel spur gears)
6491X	Gear, 18-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
6494X	(compatible with steel spur gears)
04947	Gear, 20-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (compatible with steel spur gears)
6495X	Gear, 22-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
04557	(compatible with steel spur gears)
6496X	Gear, 24-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
040070	(compatible with steel spur gears)
6447R	Spur gear, 46-tooth, steel (wide-face, 1.0 metric pitch)
6448R	Spur gear, 50-tooth, steel (wide-face, 1.0 metric pitch)
6449X	Spur gear, 54-tooth, steel (1.0 metric pitch)
6449R	Spur gear, 54-tooth, steel (wide-face, 1.0 metric pitch)
	Steering Components
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)
7747	Servo horn, steering/ linkage, steering (46mm, assembled with pivot
	balls)
7746	Steering bellcranks/ bellcrank support/servo saver/ servo saver
	spring/ draglink/ 3x20mm shoulder screws (2)
7746X	Steering link, steel/ servo saver spring, heavy duty (use with
7740	#2085X metal gear servo)
7748	Toe links, molded composite, 173mm (158mm center to center)
7748X	(black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum,
11407	stronger than titanium) (157mm) (2)/ rod ends, assembled with
	steel hollow balls (4)/ aluminum wrench, 10mm (1)
7748G	Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum,
7748G	Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with
7748G	
7748G 7748R	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum,
	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with
	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum,
	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7748R	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SUSUCHSION LINK(20C
	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) <u>SUSIGNSION Link(AUG</u> Insert, threaded steel (replacement inserts for #7748G, 7748R,
7748R	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SIIS [GIIS[0]] [GIIS[0]] [GIIS[0]] Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1)
7748R	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SIISIGISION Link(LIG Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert)
7748R 7798	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SIIS [GIIS[0]] [GIIS[0]] [GIIS[0]] Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1)
7748R 7798	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SIIS [16] [5] [16] [16] [16] [16] Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement
7748R 7798 7797	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SIIS(101)(101)(101)(101)(101)(101)(101)(101
7748R 7798 7797 7743	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SIISICALS (0)/ Comparison (1)/ (200) Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4)
7748R 7798 7797 7743	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) <u>SUSICINSION Link(AGC</u>) Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm
7748R 7798 7797 7743 7740 7742	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) <u>SIIS (1615 (01) [11] (19</u>) Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2)
7748R 7798 7797 7743 7740 7742 7741	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) <u>SIIS(1615(01))(11)(6116</u>) Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pins, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2)
7748R 7798 7797 7743 7740 7742	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SIIS(101)(101)(101)(101)(101)(101)(101)(101
7748R 7798 7797 7743 7740 7742 7741 7748	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SIISIGISION Link(AUG) Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2)
7748R 7798 7797 7743 7740 7742 7741	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SIISICATED IN [1] [2] [3] Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum,
7748R 7798 7797 7743 7740 7742 7741 7748	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) <u>SIIS (GIS (01) [1]] [4] [4] [6</u> Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with
7748R 7798 7797 7743 7740 7742 7741 7748 7748X	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) <u>SIIS (16) (16) (16) (16) (16)</u> Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pins, st, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7748R 7798 7797 7743 7740 7742 7741 7748	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) <u>SIISIIGINIMARA</u> Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pins set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum,
7748R 7798 7797 7743 7740 7742 7741 7748 7748X	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SIISIGISION Link(2000) Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with
7748R 7798 7797 7743 7740 7742 7741 7748 7748X 7748X	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SIISIGISION Link(LIGE Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7748R 7798 7797 7743 7740 7742 7741 7748 7748X	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) <u>SIISIGINIIIIII(2196</u> Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7748R 7798 7797 7743 7740 7742 7741 7748 7748X 7748X	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) <u>SIIS (16) SOIT Link(10)6</u> Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7748R 7798 7797 7743 7740 7742 7741 7748 7748X 7748X	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) <u>SIIS (16) (11) (11) (19)6</u> Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pins, st, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7748R 7798 7797 7743 7740 7742 7744 7748 7748X 7748G 7748R	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) <u>SIISIGINIUMIALS</u> Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pins et, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7748R 7798 7797 7743 7740 7742 7741 7748 7748X 7748G 7748G 7748R	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) <u>SIIS:IGISION Link(AJGG</u> Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pins, et, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Doe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Doe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ alu
7748R 7798 7797 7743 7740 7742 7741 7748 7748X 7748G 7748G 7748R	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) <u>SIIS (16150) IIII (1996</u> Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Declinks, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Declinks, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Declinks, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7748R 7798 7797 7743 7740 7742 7741 7748 7748X 7748G 7748G 7748R	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) <u>SIISIIGIISIOII Link(AUG</u>) Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Declinks, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Declinks, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7748R 7798 7797 7743 7740 7742 7741 7748 7748X 7748G 7748G 7748R	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) <u>SIISIIGIISIOII Link(AUG</u>) Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Declinks, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Declinks, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7748R 7798 7797 7743 7740 7742 7744 7748 7748X 7748G 7748G 7748R	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) <u>SIISIGISIOIIIII(A196</u> Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pins et, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) De links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) De links, X-Maxx® (TUBES ItCeIIIS Decal sheet, racing sponsors Official Team Traxxas® racing decal set (flag logo/ 6-color) Traxxas® racing banner, red & black (3x7 feet) ITICES & Wheels
7748R 7798 7797 7743 7740 7742 7741 7748 7748X 7748G 7748G 7748R	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) <u>SIISICITSION Link(AUC)</u> Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)
7748R 7798 7797 7743 7740 7742 7744 7748 7748X 7748G 7748G 7748R	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) SIISIGISION Link(AUG) Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Declinks, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Declinks, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Declinks, X-Maxx® TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum stronger
7748R 7798 7797 7743 7740 7742 7741 7748 7748X 7748G 7748R 7748R	stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) <u>SIISICITSION Link(AUC)</u> Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1) right threaded insert) Rod ends (4) (assembled with steel pivot balls) (replacement ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) Suspension pin retainer (4) Suspension pin set, front or rear corner (hardened steel), 4x85mm (1), 4x47mm (3), 4x33mm (2) (qty 4, #7740 required for complete set) Suspension pin set, shock mount (front or rear, hardened steel), 4x25mm (2), 4x38mm (2) Suspension pins, 4x85mm (hardened steel) (2) Toe links, molded composite, 173mm (158mm center to center) (black) (2) Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)

Page 4 X-Maxx®: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 77086-4) Parts List

Page 4	
7773	Tires & wheels, assembled, glued (X-Maxx® black wheels,
	paddle tires, foam inserts) (left & right) (2)
7772G	Tires & wheels, assembled, glued (X-Maxx® green wheels, Maxx® AT tires, foam inserts) (left & right) (2)
7772T	Tires & wheels, assembled, glued (X-Maxx® orange wheels, Maxx® AT tires, foam inserts) (left & right) (2)
7772R	Tires & wheels, assembled, glued (X-Maxx® satin chrome wheels, Maxx® AT tires, foam inserts) (left & right) (2)
7770X	Tires, Maxx® AT (left & right) (2)/ foam inserts (2)
7757	Wheel hex clips (6)
7756	Wheel hubs, hex (2)/ hex clips (2)
7756X	Wheel hubs, hex, aluminum (blue-anodized) (4)
7756G	Wheel hubs, hex, aluminum (green-anodized) (4)
7756R	Wheel hubs, hex, aluminum (red-anodized) (4)
7758A	Wheel nuts, splined, 17mm, serrated (black-anodized) (4)
7758	Wheel nuts, splined, 17mm, serrated (blue-anodized) (4)
7758G	Wheel nuts, splined, 17mm, serrated (green-anodized) (4)
7758T	Wheel nuts, splined, 17mm, serrated (orange-anodized) (4)
7758R	Wheel nuts, splined, 17mm, serrated (red-anodized) (4)
5480X	Wheel wrench, splined, 17mm
7771	Wheels, X-Maxx®, black (left & right)
	Transmission Components
7796	Center drive, torque-biasing (assembled)/ 17x26x5 ball bearings (2) (requires #7727X bulkheads)
7787	Covers, gear (3)
7785X	Input gear, transmission, 20-tooth/ 2.5x12mm pin
7786X	Input shaft, transmission (cush drive)
5040	Oil, differential (20M wt) (standard)
7784X	Output gear, 51-tooth, metal (requires #7785X input gear)
	Traxxas Tools
3433X	Body reamer (aluminum handle)
3433	Body reamer (plastic handle)
3436	Cap, body reamer
3432	Scissors, curved tip
3431	Scissors, straight tip
8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes
	premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm, and 8.0mm), 1/4" drive
8721	Speed bit handle, medium (one piece)
8720	Speed bit handle, premium, large (rubber overmold)
8722	Speed bit handle, premium, medium (rubber overmold)
8710	Speed Bit Master Set, hex and nut driver, 13-piece, includes
	premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm, 2.0mm), cod aut drivers (4.00mm, 4.50mm, 5.00mm, 5.50mm)
	3.0mm), and nut drivers (4.00mm, 4.50mm, 5.00mm, 5.50mm, 7.00mm, 8.00mm),
8711	Speed Bit Master Set, hex driver, 7-piece straight and ball end,
	includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm,
	2.5mm, 3.0mm), 1/4" drive
8719	Speed Bit Master Set, nut driver, 6-piece, includes premium
	handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm,
9746	5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
8716	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4" drive
8716X	Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm,
	3.0mm), 1/4" drive
8715	Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm,
	2.5mm), 1/4" drive
8715X	Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm, 2.5mm, 3.0mm), 1/4" drive
3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm,
	3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut
	drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/
	driver handle
5480X	Wheel wrench, splined, 17mm
	Turnbuckles & Threaded Rods
7798	
1130	Insert, threaded steel (replacement inserts for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X) (includes (1) left and (1)
	right threaded insert)
7797	Rod ends (4) (assembled with steel pivot balls) (replacement
	ends for #7748G, 7748R, 7748X, 8542A, 8542R, 8542T, 8542X)
7748	Toe links, molded composite, 173mm (158mm center to center)
77 / 0.1/	(black) (2)
7748X	Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum,

7748X Toe links, X-Maxx® (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1) 7748G Toe links, X-Maxx® (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)

7748R Toe links, X-Maxx® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (157mm) (2)/ rod ends, assembled with steel hollow balls (4)/ aluminum wrench, 10mm (1)

If you have questions or need technical assistance, call Traxxas at:



For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com